

Příloha . 2 - Tabulka pro výpočet nabídkové ceny
Rozšíření centrálního interkomu IV

Položkový rozpočet				
Pol.	Typ	Název - popis	Počet kus	Cena za kus bez DPH
1	MADI-108 G2 SET	8-port Artist client card to connect MADI signals via coax or fiber (optional, requires SFP MADI Modul, Item Nr. 1990002, 1990003, 1990047, not included); cascadeable client card for a maximum of 64 audio channels; connector type 2x BNC or LC duplex	1	0,00 K
2	VoIP-108 G2 SET	Channel VoIP Client-Card with Ethernet- Port; multiple Audio-Coding algorithms to match VoIP parameters: Audio Quality vs. Datarate. Supports SIP	4	0,00 K
3	Connect IPx2-CAT	2-Channel Remote VoIP Interface; with Ethernet-Port and two CAT5 panel ports; for remoting of panels or VoIP 4-wires (AES). The required external power supply is included	10	0,00 K
4	RCP-1112	19" / 1RU control panel with 12 OLED colour display keys; 8 characters per key; individual volume control per key; 5 function keys; 1 shift page; master level control; 4-pin XLR headset connector; built-in loudspeaker; 3 GPI I/Os; auxiliary connector for external microphone and external loudspeaker; 2 external headset connectors and 2 analog balanced audio inputs and outputs; matrix link: BNC (75 ohms coax cable) or RJ-45 (CAT-5 cable); Option slot for future expansions; integrated power supply; overall depth: 80mm	2	0,00 K
5	DCP-1116	Desktop control panel with 16 OLED colour display keys; 8 characters per key;	2	0,00 K
6	VCP-1012	virtual Software panel 12 keys; 8 characters per key; individual volume control per key; 1 shift page; master level control.supports Windows7, Vista, XP; USB Dongle required and included. The dongle is connected to the local USB port of the computer that runs the VCP software. One dongle can hold the licenses for multiple software modules.	3	0,00 K
7	VCP-1312	The Riedel Virtual Control Panel brings the reliability and flexibility of Riedel Intercom Solutions to your mobile device.Turn your iOS or Android device into a fully-featured 12-key Intercom Panel over a WiFi network. Connectivity over mobile networks will follow as a free update of thisapp.Each key offers an 8 character display and individual volume control for intuitive volume adjustments. The use of the shift page doubles the number of programmable keys to 24.	1	0,00 K

8	CCP-1116	Commentary desktop control panel for two commentators with 16 OLED colour display keys and additional commentary controls; 8 characters per key; individual volume control per key; 5 function keys; 1 shift page; master level control; built-in loudspeaker; 1 GPI relay output and 1 GPI input on rear XLR-5f socket; auxiliary XLR-3 connectors for external microphone and external loudspeaker; matrix link: BNC (75 ohms coax cable) or RJ-45 (CAT-5 cable); 2 external XLR-4m headset connectors and 2 high-performance inputs for commentary HS (XLR3f/1/4inch) inputs with +48V phantom power and 20dB pad; 2 rear XLR-3f AUX inputs and other commentators' signals can be separately activated and added; all monitor signals can be separately positioned L-M-R with rear switches; illuminated On-Air and Mic-Mute keys; 5 separate transformer balanced XLR-3m outputs for Mic Direct A/B, On-Air A/B and On-Air A+B; integrated power supply; alternative XLR-4m 12VDC power supply input	1	0,00 K
9	MIC-30	Electret microphone for Intercom/Performer panels; cardioid; length: 30cm	8	0,00 K
10	RSP-2318	19" / 1RU Smartpanel Platform with 18 keys; 3 multi-colored, high resolution, multitouch displays; integrated power supply; studio grade mic preamps; 2 headset connectors (exchangeable XLR connector on front); high quality loudspeaker; 3 GPI- In; 3 GPI-Out; 2 analog 4-Wire; Matrix link: AES67/AVB; HDMI; SD-Card Slot; option slot; 2 USB ports; overall depth: 78,5mm; gooseneck microphone required; requires matching software Application (e.g. RSP-2318-APP-PRO 1220210)	4	0,00 K
11	RSP-2318-APPPRO	Intercom App for Smartpanel RSP-2318; Turns the RSP-2318 platform into an Intercom Panel; supports 18 keys; individual volume control; supported connectivity: AES67/AVB, Ethernet; 2 Headsets, 2 USB ports, 2 analog 4-Wire, expansion panels connectivity, option slot, 3 GPI-In, 3 GPI-Out; purchase of Update Fee (RSP-2318-UF- PRO 1220310)recommended	4	0,00 K
12	SPX-AES	Expansion module for the expansion slot in the RSP Smartpanel platform. The module offers an AES3 interface (BNC and RJ-45 Connector), that allows connectivity to Riedel Digital Intercom Matrices via AES3.	4	0,00 K
13	Shipping	Shipping costs	1	0,00 K
		CELKOVÁ CENA BEZ DPH		
		Sazba DPH		

		Celková výze DPH
		Celková cena s DPH

Uchaze vyplní výechna ýlut ozna ená pole v tabulce

[illegible]

0,00 K
0,00 K
0,00 K
0,00 K
0,00 K
0,00 K
0,00 K
0%

0,00 K

0,00 K