

Příloha č. 3 - Tabulka pro výpočet nabídkové ceny

Položka	Výrobce	Typ	Název - popis	ks	Jednotková cena	Celková cena
1	Riedel	1010003	MFR-064 G2 19"/ 3 RU Artist mainframe with alarm relays and fan unit holds max. 2x CPU cards, 8 client cards or GPI cards requires 1x CPU card and 1x power supplies for operation 2x CPU cards and 2x power supplies required for redundant operation	1	0 Kč	0 Kč
2	Riedel	1040005	CPU-128F G2 SET CPU card for Artist mainframes for redundancy 2 node controllers are required ber connectivity to link multiple mainframes (please select appropriate ber optic module) 10BaseT port connector (RJ45) for con guration alarm outputs	1	0 Kč	0 Kč
3	Riedel	1040013	VoIP-108 G2 SET 8-Channel VoIP Client-Card with Ethernet- Port multiple Audio-Coding algorithms to match VoIP parameters: Audio Quality vs. Datarate. Supports SIP	1	0 Kč	0 Kč
4	Riedel	1010004	PSU-064 G2 Power supply for Artist mainframe MFR-064 G2 two units are required per main- frame for PSU redundancy.	2	0 Kč	0 Kč
5	Riedel	1090002	ART-Z-SFP-CPU- MM-850-8,5-1,25Gbps 1 x LC - Duplex-Module for CPU-128F G2, 850nm, 1.25Gbit/s, opt. Budget 8,5dB (P-out = -4 to -9.5 dBm, P-in = -18 to 0 dBm) Distance to cover depending on attenuation of ber used: 50/125µm Multimode-Fiber up to: 500m (1.640ft).	2	0 Kč	0 Kč
6	Riedel	1040010	MADI-108 G2 SET 8-port Artist client card to connect MADI signals via coax or ber (optional, requires SFP MADI Modul, Item Nr. 1990002, 1990003, 1990047, not included) cascadeable client card for a maximum of 64 audio channels connector type 2x BNC or LC duplex	2	0 Kč	0 Kč
7	Riedel	1090002	ART-Z-SFP-CPU- MM-850-8,5-1,25Gbps 1 x LC - Duplex-Module for CPU-128F G2, 850nm, 1.25Gbit/s, opt. Budget 8,5dB (P-out = -4 to -9.5 dBm, P-in = -18 to 0 dBm) Distance to cover depending on attenuation of ber used: 50/125µm Multimode-Fiber up to: 500m (1.640ft).	4	0 Kč	0 Kč
8	Riedel	1210003	DCP-1016E/O Desktop control panel with 16 LED display keys 8 characters per key individual volume control per key 5 function keys 1 shift page master level control 2x 4-pin XLR headset connector built-in loudspeaker 3 GPI I/Os auxiliary connector for external microphone and external loudspeaker 2 analog balanced audio inputs and outputs matrix link: BNC (75 ohms coax cable) or RJ-45 (CAT-5 cable) integrated power supply gooseneck microphone (e.g. MIC-30 6390004) not included	1	0 Kč	0 Kč
9	Riedel	6390004	MIC-30 Electret microphone for Intercom/Performer panels cardioid length: 30cm.	1	0 Kč	0 Kč
10	Cisco	C819G-4G-GA-K9	C819G-4G-GA-K9 C819 M2M 4G LTE FOR GLOBAL	4	0 Kč	0 Kč
	Riedel	Shipping	Shipping costs	1	0 Kč	0 Kč

CELKEM (bez DPH)

0 Kč

Sazba DPH 21%

DPH

0 Kč

CELKEM (s DPH)

0 Kč

Účastník vyplní pouze žlutě označená pole.