

Příloha č. 3 - Tabulka pro výpočet nabídkové ceny

Položka:	Výrobce:	Typ:	Název - popis:	ks	Jednotková cena:	Celková cena:
1	Riedel	1040005	CPU-128F G2 SET CPU card for Artist mainframes for redundancy 2 node control- lers are required fiber connectivity to link multiple mainframes (please select appropriate fiber optic module) 10BaseT port connector (RJ45) for configuration alarm outputs Required SFP modules (Item Nr. 1090002, 1090003, 1090004) not included	1		0 Kč
2	Riedel	1090002	ART-Z-SFP-CPU- MM-850-8,5-1,25Gbps 1 x LC - Duplex-Module for CPU-128F G2, 850nm, 1.25Gbit/s, opt. Budget 8,5dB (P-out = -4 to -9.5 dBm, P-in = -18 to 0 dBm) Distance to cover depending on attenuation of ber used: 50/125µm Multimode-Fiber up to: 500m (1.640ft).	2		0 Kč
3	Riedel	1090038	ART-Z-HDLC cable HDLC cable for connecting two CPU cards within a frame	1		0 Kč
4	Riedel	1040013	VoIP-108 G2 SET 8-Channel VoIP Client-Card with Ethernet- Port multiple Au- dio-Coding algorithms to match VoIP parameters: Audio Quality vs. Datarate. Supports SIP	2		0 Kč
5	Riedel	1040008	GPI-116 G2 SET GPI Artist client card 16x relay outputs (maximum 60V 300mA) and 16x optoisolated inputs (5 - 48V) connector type SubD37	1		0 Kč
6	Riedel	1310017	Connect IPx8-CAT SET 8-Channel Remote VoIP Multiplexer with Ethernet-Port and 8 individual CAT5 panel ports for remoting a group of panels or digital VoIP 4-wires (AES) units can be linked to a Matrix VoIP Client Card	2		0 Kč
7	Riedel	1310015	Connect IPx2-CAT 2-Channel Remote VoIP Interface with Ethernet-Port and two CAT5 panel ports for remoting of panels or VoIP 4-wires (AES). The required external power supply is included	3		0 Kč
8	Riedel	1210003	DCP-1016E/O Desktop control panel with 16 LED display keys 8 characters per key individual volume control per key 5 function keys 1 shift page master level control 2x 4-pin XLR headset connector built-in loudspeaker 3 GPI I/Os auxiliary connector for external microphone and external loudspeaker 2 analog balanced audio inputs and outputs matrix link: BNC (75 ohms coax cable) or RJ-45 (CAT-5 cable) integrated power supply gooseneck micro- phone (e.g. MIC-30 6390004) not included	5		0 Kč
9	Riedel	1220500	RSP-1232HL 19" / 2RU 1200 series SmartPanel Platform with 32 hybrid lever keys for flexible workflows 2 full-color, high-resolution, mul- ti-touch key displays 1 full-color, high-resolution, multi-touch info display high-quality stereo loudspeakers 2 SFP and 2 ETH (RJ45) AES67 Matrix Link ports 2 analog 4-wire connections (RJ45) 3 GPI-In, 3 GPI-Out 2 headset connectors (XLR/RJ45) 2 Matrix connectors (RJ45/BNC) 2 USB ports MicroSD card slot depth: 95 mm / 3.7" gooseneck microphone (e.g. MIC-30 6390004) not included requires matching software application (RSP-1232HL-APP-PRO)	1		0 Kč
10	Riedel	1220525	RSP-1232HL-LIC- AES3 License to enable AES3 Intercom Matrix connectivity on the RSP- 1232HL SmartPane	1		0 Kč
11	Riedel	1220250	RSP-1232HL-APP-PRO PRO version of the Intercom Application for the RSP-1232HL. SmartPanel turns the RSP-1232HL User Interface into an Intercom Panel supports 32 keys 2 SFP and 2 ETH (RJ45) AES67 Matrix Link ports 2 analog 4-wire connections (RJ45) 3 GPI-In, 3 GPI-Out 2 headset connectors (XLR/RJ45) 2 Matrix connectors (RJ45/BNC) 2 USB ports	1		0 Kč
12	Riedel	6390003	MIC-3 Electret microphone for Intercom/Performer panels cardioid length: 3cm	5		0 Kč
13	Riedel	1090011	XLR-Patch 19"/1RU patchfield for converting 8 analog or 8 AES ports from the Artist matrix to XLR connectors	2		0 Kč
14	Cisco	1109-4PLTE2P	1109-4PLTE2P with dual LTE pluggable and 802.11ac Wi-Fi	2		0 Kč
15	Riedel	1010004	PSU-064 G2 Power supply for Artist mainframe MFR-064 G2 two units are required per main-frame for PSU redundancy.	1		0 Kč
16	Riedel	1010006	PSU-032 G2 Power supply for Artist mainframe MFR-032 G2 two units are required per main-frame for PSU redundancy.	1		0 Kč
					CELKEM (bez DPH)	0,00 Kč
					Sazba DPH	0,00 Kč
					CELKEM (s DPH)	0,00 Kč