

**Příloha č. 4 - Technická specifikace**

Položka	Výrobce	Typ	Název - popis	ks
1	Riedel	1 210 015	<b>DCP-1116</b> Desktop control panel with 16 OLED colour display keys; 8 characters per key; individual volume control per key; 5 function keys; 1 shift page; master level control; 2x 4-pin XLR headset connector; built-in loudspeaker; 3 GPI I/Os; auxiliary connector for external microphone and external loudspeaker; 2 external headset connectors and 2 analog balanced audio inputs and outputs; matrix link: BNC (75 ohms coax cable) or RJ-45 (CAT-5 cable); integrated power supply; gooseneck microphone (e.g. MIC-30 6390004) not included	5
2	Riedel	6 390 003	<b>MIC-3</b> Electret microphone for Intercom/Performer panels; cardioid; length: 3cm	5
3	Riedel	1 040 019	<b>AES67-108 G2 SET</b> Converts 8 Artist matrix AES ports into unidirectional AES67 streams and vice versa. The client card communicates either with other AES67 client cards or key panels. The set consists of an AES67 rear card and a AES67 front card. 1xRJ45 AES67 Ethernet 1000Base-T; 1xRJ45 ETH 100Base-T; 1x BNC Wordclock Out	2
4	Lynx Technik	AG yellobrik OET 1510 MM	Lynx Technik AG yellobrik OET 1510 Ethernet to 1Gbit Fiber Transceiver Switch	1
5	Riedel	1 090 200	<b>NSA-001D</b> The NSA (Network Stream Adapter) in a PoE (Power over Ethernet) enabled, bidirectional AES67 to AES3 converter. The NSA also enables 1000 and 1100 series Intercom panels to be connected via AES67 to a Riedel ARTIST Intercom matrix. The NSA can be powered redundant or alternative with a power adapter (1090029)	1
6	Riedel	1 390 024	<b>Luminex GigaCore 26i switch (LU 01 00052-POE)</b> 24-port RJ45 AES67 GigE Switch with 6x SFP fibre cages with QoS, PTPv2, IGMP snooping, PoE+	1
6.1	Riedel	1 390 100	<b>GigaCore Multimode fiber SFP (LU 90 00871)</b> Multimode fiber transceiver SFP, 1.25G, up to 500 metres	1
7	Riedel	1390031	<b>Luminex GigaCore 10 switch (LU 0100058-POE)</b> 8-port Ethercon AES67 GigE Switch with QoS, PTPv2, IGMP snooping, PoE+ (rack mount brackets included)	1
8	Riedel	1430020	<b>BL-BPK-1006-19-EU</b> 6-key digital wireless roaming beltpack Europe version. DECT license free band (1880–1900 MHz), master & individual volume rotary controls, reply key, call light, full colour sunlight readable LED display, ADR receiver, NFC, BT, 4-pin XLR headset connector, rugged housing with rubber protectors and integrated internal antennas. Includes 1x BL-BAT re-chargeable Lithium Ion battery pack & 1x Beltclip. Excludes Headset.	4
9	Riedel	1 430 077	<b>BL-BPK-COVER-RED</b> 5x Bolero Beltpack Protection Cover Red	1

10	Riedel	1 610 006	<b>PRO-D1 (XLR4F)</b> Medium-weight headset   rotatable boom for left or right side use   comfortable   high-quality double-earpiece headset   dynamic microphone (hyper-cardioid)   4-pin XLR-female connector	3
11	Riedel	1 610 034	<b>PRO-E1 (XLR4F)</b> Medium-weight headset; rotatable boom for left or right side use; comfortable; high-quality single-earpiece headset; dynamic microphone (hyper-cardioid); 4-pin XLR-female connector	1
12	Riedel	1431000	<b>BL-ANT-1010-19G- EU G2</b> Active antenna for Bolero Standalone or Integrated. Europe ver- sion (Grey) with E-Ink display for up to 10 BL-BPK belt packs. DECT license free band (1880–1900 MHz)   AES67 layer 3 IP network mode via Cat-5 cabling   optional Standalone daisy chain network mode via Cat-5 cabling   PoE+ (802.3at, type 2, class 4, 15-30W) power, local DC or PoC daisy chain remote power	2
13	Riedel	1439150	<b>BL-ANT-APP- STANDALONE</b> Standalone entitlement for a Bolero antenna	1
14	Riedel	1090201	<b>NSA-002A</b> Robust 4-wire box with 6 analog inputs, 6 analog outputs   3 GPI-In, 3 GPI-Out   half 19" rackmountable or throwdown box with bumpers   AES67 layer 3 IP network via CAT-5 cabling   incl. internal universal PSU	1
15	Riedel	1090210	<b>SPK-001 – Stage- box Protection Kit</b> - 4x protection bumpers for half 19" devices (e.g. NSA-002A)	1
16	Riedel	1430017	<b>BL-EPS-1001-00</b> Bolero external power supply for single BL-ANT Antenna. Required if PoE is not available.	2
17	Riedel	1430040	<b>BL-CHG-1005-R</b> 5-bay tabletop or wall mount charger for BL-BPK or spare battery BL-BAT, network capable, internal universal PSU included.	1